



SANODAL® GREEN 3LW

Sanodal Green 3LW produces an attractive green shade that can be suitable for exterior architectural components.

PROPERTIES:

Chemical description:	Azo dye (granular)
Light fastness:	Architectural (8+)
Weather fastness:	Excellent
Heat fastness:	Moderate up to 400° F.

RECOMMENDED APPLICATION DETAILS:

Concentration:	0.5 – 3.0 g/l
pH range:	5.0 – 6.0
Buffering:	Anodal® Dye Buffer Liquid (not required)
Temperature:	120° - 160° F.
Immersion time:	2 - 20 min.

For architectural quality finishes, please refer to the processing requirements as described in the Reliant bulletin, the *Sanodal System*.

PREFERRED SEALING METHODS:

Hot:	Anodal ASL or Anodal AS
Medium:	Anodal MS-1 New or Anodal MTS Plus
Cold:	Anodal CS-2, Anodal CS-2N or Anodal CS3

PRECAUTIONS:

The dye solution is very sensitive to contamination by aluminum and other metal salts as well as sulfates. Tap water should not be used to make up this dye bath. Thorough rinsing before dyeing and care to eliminate drag-in is strongly advised.

ENVIRONMENTAL CONSIDERATIONS:

This RoHS compliant product contains chromium as an integral part of the dye. The preferred method of disposal is described in the Reliant bulletin, the *Anodal WT System*.

Recommendations, notices or instructions as to handling, use, storage or disposal of this product, including its use alone or in combination with other products, or as to any apparatus or process for its use are based upon information believed to be reliable. No liability is taken with respect to any such recommendations or instructions. Sole and exclusive warranty is that products comply with published chemical and physical specifications as provided on the certificate of analysis. No other warranties, either express or implied are given.