



## ANODAL® MS-1A LIQUID

**Anodal MS-1A Liquid** is an organic additive for use with seal solutions: *Anodal MS-1 New*, *Anodal MTS Plus*, and *Anodal ES-1*. The addition of *Anodal MS-1A Liquid* to these sealing baths can have the following beneficial effects:

- Improved rinsing action of sealed parts
- Reduced sealing smut
- Improved sealing efficiency
- Extended life of sealing bath

### **PHYSICAL PROPERTIES:**

Specific gravity: 1.05 (8.7 lbs/gallon)

### **APPLICATION CONDITIONS:**

Periodic additions to the products listed above may significantly extend the life of the seal baths. Typical maintenance doses are 20-40 oz per 1,000 gallon tank volume on a weekly basis. If a water break-free surface is noticed on the parts after seal rinse, than a half gallon per 1,000 gallon tank volume should be added immediately.

### **PRECAUTIONS:**

To guard against the possible yellowing of clear coatings it is important that the anodizing conditions be kept within normal limits, especially with respect to current density and electrolyte temperature. Additional information about this may be obtained from your Reliant Technical Representative.

Recommendations, notices or instructions as to handling, use, storage or disposal of this product, including its use alone or in combination with other products, or as to any apparatus or process for its use are based upon information believed to be reliable. No liability is taken with respect to any such recommendations or instructions. Sole and exclusive warranty is that products comply with published chemical and physical specifications as provided on the certificate of analysis. No other warranties, either express or implied are given.