



SANODYE® GREEN AX

Sanodye Green AX produces an attractive deep green color. Although it is a mixture it has good stability and long tank life.

PROPERTIES:

Chemical description:	Azo dye blend (powder)
Light fastness:	Good (6)
Heat fastness:	Good up to 250°F.

RECOMMENDED APPLICATION DETAILS:

Concentration:	0.5 - 5.0 g/l
pH range:	5.5 - 6.0
Buffering:	~1% Ammonium Acetate Liq.
Temperature:	140° - 160° F.
Immersion time:	2 - 20 minutes

PREFERRED SEALING METHODS:

Hot:	Anodal ASL or Anodal AS
Medium:	Anodal MS-1 New or Anodal MTS Plus
Cold:	Anodal CS-2, Anodal CS-2N or Anodal CS3

PRECAUTIONS:

The solution is fairly resistant to drag-in contamination but normal care in rinsing is advised for maximum tank life. Algae or fungi growth may become a problem if the tank is not kept sterile by boiling the solution occasionally. The shade may be adjusted with occasional additions of *Sanodye Blue A* or *Sanodye Orange 2B*.

ENVIRONMENTAL CONSIDERATIONS:

This is a RoHS compliant product that contains no heavy metals.

Recommendations, notices or instructions as to handling, use, storage or disposal of this product, including its use alone or in combination with other products, or as to any apparatus or process for its use are based upon information believed to be reliable. No liability is taken with respect to any such recommendations or instructions. Sole and exclusive warranty is that products comply with published chemical and physical specifications as provided on the certificate of analysis. No other warranties, either express or implied are given.